

Solid State High Power Amplifier Systems

2-18GHz /37 dB Gain/37 dBm Psat/220AC

Model: TLPA2G18G-37-37-BC

TLPA2G18G-37-37-BC is a solid state high power amplifier systems provides high output power and high gain across the 2 to 18 GHz frequency range. The amplifier features a built-in 220V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Wide Band: 2-18 GHz
- Gain: 37dB Min
- Psat Output Power:37dBm Min
- Protection:Over TEM,over voltage, over current ,over VSWR protection.
- 50 Ohm Matched Input / Output

Electrical Characteristics:

Parameter	Symbol	Min	Typ	Max	Units
Frequency range	BW	2-18			GHz
Gain	GP	37			dB
Gain flatness	ΔGL		± 3		dB
Output Psat	Psat	37			dBm
Spurious	Spur		-60		dBc
Harmonics	HAM		-15		dBc
Input VSWR	VSWRin			2.0	:1
AC Voltage	Vac	220			V AC
Power consumtpion	Pdiss	120			A
Impedance	I/O-IMP	50			Ohms

Mechanical Specifications:


Parameter	Value	Units
Input /Output Connector	SMA Female/SMA Female	
AC Power Interface	Air switch	
Size	19 Inch 2U	
Weight	20	Kg

Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	260V AC
RF Input Power	+5 dBm
ESD sensitivity (Hbm)	Class 0, passed 150V

Outline Drawing:

Unit:mm



Key Features:

Parameter	Advantages
Control	RS422
Protection functions	1,Over TEM 2,Over voltage 3,Over current protection 4,Output mismatch
Control functions	1,Power setting On/Off 2,ALC
Cooling system	Built in Cooling system,forced air cooling

Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature*	-20		+50	°C
Non-operating Temperature*	-45		+65	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD- 810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

Ordering Information:

Base Number	Description	Revision
TLPA2G18G-37-37-BC	Solid State High Power Amplifier Systems 2-18GHz,Gain:37dB,Psat:37dBm,220V AC,Built in Fan Cooling	Rev.1.0