

Solid State High Power Amplifier Systems

0.1-6GHz/37dB Gain/37dBm Psat/220V AC

Model: TLPA0.1G6G-37-37-BC

TLPA0.1G6G-37-37-BC is a solid state high power amplifier systems provides high output power and high gain across the 0.1 to 6 GHz frequency range. The amplifier features a built-in 220V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

- Features:**
- Frequency range: 0.1-6GHz
 - Gain: 37dB Min
 - Psat Output Power: 37dBm Min
 - Protection:Over TEM,over voltage, over current ,over VSWR protection
 - 50 Ohm Matched Input / Output

电气特性 Electrical Characteristics:

参数 Parameter	代码 Symbol	Min	Typ	Max	单位 Units
频率范围 Frequency range	BW	0.1-6			GHz
功率增益 Power Gain	GP	37	40		dB
增益平坦度 Gain flatness	ΔGL		±3	±4	dB
线性输出功率 Output P1dB	P1dB	33	34		dBm
饱和输出功率 Output Psat	Psat	37	38		dBm
谐波 Harmonics	HAM		-10		dBc
输入驻波 Input VSWR	VSWRin		1.5	2.0	:1
交流电压 AC Voltage	Vac	110	220		V AC
功耗 Power Consumption	Pdiss		30	60	W
阻抗 Impedance	I/O-IMP	50			Ohms



机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/ SMA Female	
尺寸 Size	274*214*94	mm
重量 Weight	≤5	Kg

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm



主要功能 Key Features:

参数 Parameter	特点 Advantages
控制功能 Control functions	1, Power setting On/Off
内置保护功能 Protection functions	1,Over TEM 2,Over voltage 3,Over current 4,Over VSWR
冷却系统 Cooling system	Built in Cooling system,forced air cooling

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	°C
存储温度 Non-operating Temperature*	-50		+70	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA0.1G6G-37-37-BC	Solid State High Power Amplifier Systems 0.1-6GHz,Gain:37dB,Psat:37dBm,220V AC,Built in Fan Cooling	Rev.1.1